



SolarEdge Single Phase Inverters

SE2200 - SE6000



INVERTERS

Specifically designed to work with power optimizers

- Superior efficiency (97.6%)
- Small, lightweight and easy to install
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- IP65 – Outdoor and indoor installation
- Fixed voltage inverter, DC/AC conversion only



Single Phase Inverters

SE2200 - SE6000

	SE2200	SE3000	SE3500	SE4000	SE5000	SE6000	
OUTPUT							
Rated AC Power Output	2200	3000	3500	4000	5000	6000	VA
Maximum AC Power Output	2200	3000	3500	4000	5000	6000	VA
AC Output Voltage (Nominal)	220 / 230						Vac
AC Output Voltage Range	184 - 264.5						Vac
AC Frequency (Nominal)	50 / 60 ± 5						Hz
Maximum Continuous Output Current	12	16.5*	19.5*	22*	27	27	A
Residual Current Detector / Residual Current Step Detector	300 / 30						mA
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes						
INPUT							
Recommended Maximum DC Power** (Module STC)	3000	3750	4350	5000	6250	7500	W
Transformer-less, Ungrounded	Yes						
Maximum Input Voltage	500						Vdc
Nominal DC Input Voltage	350						Vdc
Maximum Input Current	8.5	11.5	13.5	15.5	19.5	23	Adc
Reverse-Polarity Protection	Yes						
Ground-Fault Isolation Detection	600kΩ Sensitivity						
Maximum Inverter Efficiency	97.6						%
European Weighted Efficiency	97.6	97.6	97.5	97.5	97.4	97.4	%
Nighttime Power Consumption	< 2.5						W
ADDITIONAL FEATURES							
Supported Communication Interfaces	RS485, RS232, Ethernet, Zigbee (optional)						
STANDARD COMPLIANCE							
Safety	IEC-62103 (EN50178), IEC-62109						
Grid Connection Standards	VDE 0126-1-1, VDE-AR-N-4105, AS-4777, RD-1663, DK 5940						
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B						
RoHS	Yes						
INSTALLATION SPECIFICATIONS							
AC Output	Cable Gland - diameter 9-16						mm
DC Input	1 MC4 pair			2 MC4 pairs			
Dimensions (HxWxD)	540 x 315 x 172			540 x 315 x 191			mm
Weight	20.2			21.7			kg
Cooling	Natural Convection						
Noise	< 50						dBA
Operating Temperature Range	-20 - +50 (M40 version -40 - +50)						°C
Protection Rating	IP65 - Outdoor and Indoor						
Bracket Mounted (Bracket Provided)							

* For inverters with an AC current limit of 16A please refer to the "SE3000-4000-16A Inverter" datasheet.

** Limited to 125% for locations where the yearly average high temperature is above 25 °C and to 135% for locations where it is below 25 °C. For detailed information, refer to http://www.solaredge.us/files/pdfs/inverter_dc_oversizing_guide.pdf

